

Dry Scroll Vacuum Pump

ISP Series



Scroll Meister Dry Scroll Vacuum Pump ISP-50

ISP-50





ISP-90






ISP-250C









Trade name	Oil free scroll vacuum pump						
Model			ISP-50-SV1	ISP-50-SV2	ISP-90	ISP-250C	
Pumping speed	L/min (CFM) 50/60Hz		50/60 (1.8/2.1)		90/108 (3.2/3.8)	250/300 (8.8/10.6)	
Ultimate pressure	Pa(Torr)		≦ 15 (1.1x10 ⁻¹)		≦5 (3.7x10 ⁻²)	$\leq 1.6 (1.2 \times 10^{-2})$	
Motor power	W		100		150	400	
Voltage	V	1Ph	100,115 200,230		100,115,200,230		
		3Ph		_	-	200,208,230,380,415,460	
Noise level	dB (A)		48		52	58	
Noise level (at air-flush)			57		57	66	
Weight	kg	1Ph	12		14	25	
		3Ph	-		-	23	
Leak tightness	Pa · m³/s		≦ 1.0x10 ⁻⁷		≦ 1.0x10 ⁻⁵	≦ 1.0x10 ⁻⁵	
Water vapor capacity	g/day		3		5	25	
Air flush	L/min		4		9	10	
Inlet connection	NW		25				
Outlet connection	NW		16				
Cooling system			Air-cooled			ed	
Ambient temperature	°C ,	/ °F			5 ~ 40 / 41 ~ 104		




ISP-90




ISP-250C



Pumping speed




















ISP-500C






ISP-500C



ISP-1000




ISP-1000





Pumping speed



Trade name			Oil free scroll vacuum pump		
Model			ISP-500C	ISP-1000	
Pumping speed	L/min (CFM) 50/60Hz		500/600 (17.7/21.2)	1000/1200 (35.3/42.4)	
Ultimate pressure	Pa(Torr)		≦ 1 (7.5 x10 ⁻³)	≦ 1 (7.5 x10 ⁻³)	
Motor power	W		600	1400	
Voltage	V	1Ph	100,115,200,230	-	
		3Ph	200,208,230,380,415,460		
Noise level	40	/A)	60	67	
Noise level (at air-flush)	ub	(A)	68	74	
Weight	l.a.	1Ph	44	-	
rveignt	kg	3Ph	38	60	
Leak tightness	Pa · m³/s		≦ 1.0x10 ⁻⁵		
Water vapor capacity	g/day		25		
Air flush	L/min		10		
Inlet connection	NW		40		
Outlet connection	NW		25	40	
Cooling system			Air-cooled		
Ambient temperature	°C / °F		5 ~ 40 / 41 ~ 104	10 ~ 40 / 50 ~ 104	

Air Flush



Air Flush

Purpose for Air Flush - Pumping humid gas with a vacuum pump can cause condensed moisture to remain in the pump. This remaining moisture can cause a failure to the pump or ultimate pressure. The Air Flush operation is necessary to remove remaining moisture. The Air Flush operation not only removes the remaining moisture but recovers ultimate pressure.


Applications


- Sputtering equipment, Vacuum deposition equipment, Ion plating equipment
- Gas recovery devices
- Leak detectors
- Device Handling system
- Surface modification, Electron beam process
- Vacuum furnace, Heat treatment furnace
- Laboratory use
- Vacuum packaging machine
- Others

Synchrotron Facility



www.airzap.com.br







Precaution on Usage

This vacuum pump is suitable for use on **Clean** processes only.

Do not use explosive, flammable, toxic or corrosive substances or substances which contain chemicals, solvents or particles.

ANEST IWATA will not perform maintenance work on pumps which have used hazardous substances. Do not disassemble, reassemble or alter pump and parts on user's side.

Be sure to read instruction manual and understand it fully before use.

When maintenance interval has been reached, be sure to contact our distributor who sold it to you.

The guarantee period is based on instruction manual. Maintenance interval and the guarantee period are different.

Prec

Precaution on installation

Danger of explosion and fire

Install in an area which is not exposed to explosives, flammable gas, or other related things. Pumps which are shown in this catalog do not have breaker for avoiding motor burnout by installing, Avoid motor burnout using breaker.

Electric source cord is not included in the pump. Use electric source cord which is instructed by instruction manual.

This vacuum pump is required maintenance by interval which is shown on the instruction manual. Install the pump where it has enough ventilation and available maintenance.

distributed by:





COMPRESSORES DE AR

AIRZAP-ANEST IWATA IND. E COM. LTDA.

Rua Prof. Estevan Lange Adrien, 648 Jd. Stahlberg - Limeira-SP Tel: +55 19 3453-4177 Fax: +55 19 3453-4178 www.airzap.com.br