



# NOZZLE TIP



Fluid output of NT2505 is as follows ;  
 25cm×0.5ml/sec/cm=12ml/sec.  
 12.5 ml/sec×60sec=750 ml/min.(0.75liter/min.)  
 ※Fluid output is for lacquer primer at  
 100kgf/cm<sup>2</sup> (1,400psi) of 40sec. viscosity.

## Selection Table of Standard Nozzle Tip and Airless Model

tip number	fluid output		Pattern width cm (inch)	equivalent orifice dia. mm	Airless Model														TT-3B Turn Tip Cleaner Exclusive nozzle tip	Free-Pattern Tip					
	mℓ/sec	ℓ/min			EX-400 EX-401	EX-700		EX-900		EX-900EB (※ 1)	EX-2200 (※ 1)	EX-2200E (※ 1)	ALS-122 123	ALS-331B 332B 333B	ALS-431B 432B 433B	ALS-453B	ALS-653								
NT1003	3	0.18	7~13	0.20	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
NT1004	4	0.24		0.23	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
NT1005	5	0.30		0.25	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
NT1006	6	0.36		0.29	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
NT1007	7	0.42		0.31	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
NT1503	4.5	0.27	13~18	0.25	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	NT-311B		
NT1504	6	0.36		0.29	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT1505	7.5	0.45		0.32	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT1506	9	0.54		0.34	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT1507	10.5	0.63		0.36	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2003	6	0.36	18~23	0.29	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	NT-413B	
NT2004	8	0.48		0.32	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2005	10	0.60		0.36	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2006	12	0.72		0.39	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2007	14	0.84		0.43	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2009	18	1.08		0.47	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2011	22	1.32		0.53	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2013	26	1.56		0.56	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2503	7.5	0.45		23~28	0.32	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2504	10	0.60			0.36	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
NT2505	12.5	0.75	0.40		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2506	15	0.90	0.44		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2507	17.5	1.05	0.47		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2509	22.5	1.35	0.53		●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2511	27.5	1.65	0.58		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT2513	32.5	1.95	0.63		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3003	9	0.54	28~33	0.34	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	NT-515B		
NT3004	12	0.72		0.39	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3005	15	0.90		0.44	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3006	18	1.08		0.47	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3007	21	1.26		0.51	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3009	27	1.62		0.58	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3011	33	1.98		0.64	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3013	39	2.34		0.70	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3016	48	2.88		0.78	●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3019	57	3.42		0.87	●	●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3022	66	3.96		0.94	●	●	●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3503	10.5	0.63		33~38	0.36	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3504	14	0.84	0.43		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3505	17.5	1.05	0.47		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	NT-617B		
NT3506	21	1.26	0.51		△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3507	24.5	1.47	0.55		●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	NT-821B	
NT3509	31.5	1.89	0.62		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3511	38.5	2.31	0.70		●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3513	45.5	2.73	0.77		●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3516	56	3.36	0.85		●	●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3519	66.5	3.99	0.94		●	●	●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT3522	77	4.62	1.02	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
NT4003	12	0.72	38~43	0.39	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
NT4004	16	0.96		0.45	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4005	20	1.20		0.50	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4006	24	1.44		0.55	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4007	28	1.68		0.59	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4009	36	2.16		0.67	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4011	44	2.64		0.76	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4013	52	3.12		0.82	●	●	●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4016	64	3.84		0.92	●	●	●	●	●	●	△	●	●	●	●	●	●	●	●	●	●	●	●		
NT4019	76	4.56		1.01	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
NT4022	88	5.28		1.09	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		

※○Marked model in R column has Reverse Turn Tip also for Turn Tip Cleaner. ※Nozzle tip can be used in ● marked model. ※△ suitable but subject to condition.  
 ※1 Production end model

Models, specifications and photos are subject to change without notice.



3176, Shinyoshida-cho, Kohoku-ku,  
 Yokohama 223-8501, Japan  
 Tel: 045-591-1118 Fax: 045-591-1137  
<http://www.anest-iwata.co.jp/>

